



U.S. Department
of Transportation
**Research and
Special Programs
Administration**

400 Seventh St., S.W.
Washington, D.C. 20590
APR 6 2001

DOT-E 12580
(FIRST REVISION)

EXPIRATION DATE: January 31, 2003

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Matheson Tri-Gas Incorporated
East Rutherford, NJ
2. PURPOSE AND LIMITATION:
 - a. This exemption authorizes the transportation in commerce of certain non-DOT specification foreign cylinders which are charged for export only. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
 - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.301(j)(1) and 173.338 in that the prescribed non-DOT specification foreign cylinders authorized herein to be charged for export are welded instead of seamless cylinders.
5. BASIS: This exemption is based on the application of Matheson Tri-Gas Incorporated dated January 16, 2001, submitted in accordance with § 107.105 and the public proceeding thereon.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

APR 6 2001

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Tungsten hexafluoride	2.3 (Hazard Zone B)	UN2196	N/A

7. SAFETY CONTROL MEASURES:a. PACKAGING - Packagings prescribed are:

(1) Non-DOT specification foreign stainless steel welded cylinders that are designed, manufactured, and tested in conformance with the High Pressure Gas Control Law of Japan. Cylinders must be in conformance with Kanto Koatsu Yoki Mfg. Co. Ltd. drawing GHS-CIF₃-95036 and design criteria on file with the Office of Hazardous Materials Exemptions and Approvals. The valve outlet must be capped or plugged.

(2) Cylinders must have a maximum service pressure of 252.4 psi (1.74 MPa) and a minimum design burst pressure of 1528.7 psi (10.54 MPa).

b. OPERATIONAL CONTROLS -

(1) The cylinders may only be charged with Tungsten hexafluoride in the United States and shipped solely for export.

(2) Cylinders must be shipped in a strong outside packaging complying with the provisions of § 173.40(d).

(3) The shipping paper must identify the cylinders with the exemption number "DOT-E 12580" and must carry the following certification: "This cylinder has [These cylinders have] been retested and refilled in accordance with DOT requirements for export."

(4) Cylinders must be transported by dedicated truck from Longmont, Colorado to the Matheson Tri-Gas facility in Newark, California.

(5) Emergency response information provided with the shipment and available via an emergency response telephone number must indicate that the cylinders are not fitted with pressure relief devices and provide appropriate guidance for exposure to fire.

8. SPECIAL PROVISIONS:

a. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

b. MARKING - The outside of each package must be plainly and durably marked "DOT-E 12580" and "For Export Only".

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle and cargo vessel.

10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this exemption.

11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:

- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when this exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:



Robert A. McGuire
Associate Administrator for
Hazardous Materials Safety

APR 6 2001

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W.; Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

PO: cwf/AM